

Network Camera Firmware

Version: V5.5.72

Release Note (**External**)

(2018-12-20)

Firmware Basic Information	Firmware Version:	V5.5.72 build181213
	SDK Version:	V5.3.6.35_build20180830
	Play Library (PlayCtrl.dll)	V7.3.5.31 build20180130
	Encapsulation Library (SystemTransform.dll)	V2.5.2.13 build20180110
	Voice intercom library (AudioIntercom.dll)	V1.4.0.6
	iVMS-4200	V2.6.11.5Build20180905
	IE Client version	V4.0.1 build 181019 plugin:V3.0.6.50

Hikvision Firmware V5.5.72 Features

**for DS-2CD2XX6 Cameras*

1. Improved Features

- Fixed the non-main stream RTSP live viewing failure while the device is launching with sub stream under H.265.
- Fixed the web component probabilistically fails to show SD card's status while the IPC is launched with some type of SD cards on.

Compatibility Update

- **HIKCGI version: V2.0;**
- **ISAPI version: V2.4;**
- **ONVIF version: V1612, official test tool version: V1701;**
- **Milestone:**
 1. Milestone Enterprise 8.1a(10.2a), Milestone drive version (Driver 9.6, test HIKCGI
 2. Milestone software version (Milestone Corporate 11.3a), Milestone drive version (Driver 9.6), test HIKCGI
- **Avigilon:**
 1. Control Center: V6.6.2.4
 2. Test ONVIF.
- **Excaqvision:**
 1. Version: 9.0.3 124768
 2. Protocol: HIKCGI, ONVIF
- **Intellect:** V4.10.3
- **Digifort:** V7.2
- **Axxon:** AxxonNext-4.0.2.5237
- **NAS(Only test for Brainaire):**

DS-A2016R, DS-A1016RS V2.2.0-7
- **Tested NVRs:**

DS-96256NI-I24/H (baseline V3.2.8_170213_05)

96000NI-I Series NVR (V3.6.21)

E Series: DS-7732NI -E4/16P (V3.4.98)

G Series: DS-7608NI-G2/4P (V3.4.1 build 151225)

K Series(k51 platform): DS-7832N-K2 (V4.1.11)

I Series: DS-8664NI-I8 (V4.1.50)

Netra DVR: DS-9016HF-ST (V3.4.3)

Note: The compatibility of IPC and NVR models in the same NVR series is the same.
- **Tested Keyboard:**

DS-1600KI V2.0.0

DS-1006KI V1.0

Customer Impact and Recommended Action

This update refers to function/compatibility improvement and will take effect automatically after the Date of Change. We are very sorry for any inconvenience of use-habit changes caused by this action. For any questions and request for this firmware, please contact our local technical support team.

Remarks:

- Hikvision reserves the right to change, alter or withdraw the above notification without prior notice.
- Product design and specifications are subject to change without prior notice.
- The Hikvision firmware may contain defects or errors known as errata which may cause the product to deviate from published specifications. Current characterized errata are available on request.
- Hikvision is not liable for any typing or printing errors.

Hikvision Digital Technology CO., Ltd.
No. 555 Qianmo Road, Binjiang District, Hangzhou 310051,
China
Tel: +86-571-8807-5998
FAX: +86-571-8993-5635
Email: overseabusiness@hikvision.com

Supported Product List (2XX6 Series)

Product Category	Model Number	Product Description
AcuSense Turret	DS-2CD2326G1-I	2MP,IR,False alarm filter
AcuSense Turret	DS-2CD2326G1-I/SL	2MP,IR,False alarm filter
AcuSense Turret	DS-2CD2346G1-I	4MP,IR,False alarm filter
AcuSense Turret	DS-2CD2346G1-I/SL	4MP,IR,False alarm filter
AcuSense Bullet	DS-2CD2T26G1-2I/4I	2MP,IR,False alarm filter
AcuSense Bullet	DS-2CD2T26G1-4I/SL	2MP,IR,False alarm filter
AcuSense Bullet	DS-2CD2T46G1-2I/4I	4MP,IR,False alarm filter
AcuSense Bullet	DS-2CD2T46G1-4I/SL	4MP,IR,False alarm filter
AcuSense Dome	DS-2CD2126G1-I(S)	2MP,IR,False alarm filter
AcuSense Dome	DS-2CD2146G1-I(S)	4MP,IR,False alarm filter
AcuSense Bullet	DS-2CD2626G1-IZ(S)	2MP,IR,False alarm filter
AcuSense Bullet	DS-2CD2646G1-IZ(S)	4MP,IR,False alarm filter
AcuSense Dome	DS-2CD2726G1-IZ(S)	2MP,IR,False alarm filter
AcuSense Dome	DS-2CD2746G1-IZ(S)	4MP,IR,False alarm filter