

Network Camera Firmware

Version: V5.4.5

Release Note (**External**)

(2017-02-22)

Firmware Basic Information	Firmware Version:	V5.4.5 build170222
	SDK Version:	V7.3.2.74
	Play Library (PlayCtrl.dll)	V7.3.0.74
	Encapsulation Library (SystemTransform.dll)	V2.5.1.14
	RTSP Communication Library (StreamTransClient.dll)	V1.1.3.6
	Voice intercom library (AudioIntercom.dll)	V1.4.0.1
	iVMS-4200	Version 4200 V2.5.5.103 build20170119
	Web version	V3.0.6.10 build170117

Compatibility Update

- **NUUO:**

Version: V6.9.0, drive version: V5.2

- **Milestone:**

1. Milestone Enterprise 8.1a(10.1a), Milestone Corporate 10.2a
2. Milestone drive version : Device Pack 8.8

- **Avigilon:**

Avigilon Control Center: V5.10.4.6

- **Exacqvision:**

Version: 8.2.1.107318

- **Genetec Omnicast:**

Version: 4.8 SR8

- **Security Center:**

Version: 5.5 SR3

- **28181:**

V1.0.0.1/V1.0.0.5

- **Network keyboard:**

DS-1100K V2.4.0 build150827

- **Series port keyboard:**

DS-1004K V1.2.0

- **Official Tested ONVIF:**

V1601

- **NVR/DVR version accessing:**

1. Marvell E series: DS-96128N-E16 (V3.0.4_150616) (This series NVRs has been discontinued and the future version will not test)
2. Marvell F series: DS-96128N-F16 (V3.2.6 160411)
3. Hisi3535 E series: DS-7732N-E4/16P (V3.4.91)
4. Hisi3535 G series: DS-7608N-G2/4P (V3.4.1 build 151225)
5. Hisi3798 K1 series: DS-7816N-K1 (V3.4.90)
6. Hisi3536 I8 series: DS-8664N-I8 (DS-7632N-I2/16P)
7. Hisi3536 K series: V3.4.91
8. Hisi3520D\3521: DS-7608N-SHT (V3.0.17_150804)
9. Netra DVR: DS-9016HF-ST (V3.4.3)
10. 8107 plat: DS-7616N-SE (V3.0.15_150528)
11. Hisi plat F series: DS-9664N-F8/I (V3.3.4_150715)
12. Channel NVR: DS-7832N-K2 (V3.3.9_151228)
13. 96000N-I series: V3.6.0

Hikvision Firmware V5.4.5 Features

1. New Features

- **HiDDNS and IP Server are no longer supported**
- **Add Hik-Connect function, support Hik-Connect Domain Name and alarm push service.**
- **LBS address for Hik-Connect function is dev.hik-connect.com.**
- **Hik-Connect function is disabled as default.**
- **Verification code is removed from device label and verification code information is removed from QR code.**
- **During device activation or enabling Hik-Connect function for the first time, verification code should be created or changed by customers. (Rules: 6 to 12 letters (a to z, A to Z) or numbers (0 to 9), Case Sensitive.)**

The screenshot shows the Hikvision web interface. On the left, a sidebar menu has 'Local', 'System', 'Network', 'Basic Settings', 'Advanced Settings' (highlighted in red), 'Video/Audio', 'Image', and 'Event'. The main content area has tabs: 'SNMP', 'FTP', 'Email', 'Platform Access' (highlighted in red), 'HTTPS', 'QoS', and '802.1x'. Under 'Platform Access', there is an 'Enable' checkbox, a 'Platform Access Mode' dropdown set to 'Hik-Connect', a 'Server IP' field with 'dev.hik-connect.com' and a 'Custom' checkbox, a 'Register Status' dropdown set to 'Offline', and a 'Verification Code' field with 12 dots. Below the code field, a note states: '6 to 12 letters (a to z, A to Z) or numbers (0 to 9), case sensitive. You are recommended to use a combination of no less than 8 letters or numbers.'

- Add Open Source Software Licenses on web browser ->System->System Settings->About Device.

The screenshot shows the 'About Device' page in the Hikvision web interface. The sidebar menu has 'Local', 'System', 'System Settings' (highlighted in red), 'Maintenance', and 'Security'. The main content area has tabs: 'Basic Information', 'Time Settings', 'DST', 'RS-232', and 'About Device' (highlighted in red). Under 'About Device', there is a section titled 'Open Source Software Licenses' and a red button labeled 'View Licenses'.

- Newly released DS-2CD4C16FWD.
- Released the model of DS-2XE64X2FWD (2.8-12mm and 8-32mm optional), which supports Auto-focus, zoom in/out.
- The devices except DS-2CD4A24FWD (T) (4.7-94mm) support to switch Day & Night via image algorithm.
- The models of DS-2CD4A24FWD (T) (4.7-94mm), 4BX6, 4CX6, 4DX6, DS-2XE64X2 support H.265+/H.265.

2. Improved Features


- Admin account user is able to enable/disable Hik-Connect service. Admin account user is able to view verification code for Hik-Connect service on web browser or iVMS-4200.
- In DST configuration of French web page, the typo of Tuesday and Thursday is corrected.
- It supports to check the password when login in via Web.
- Admin account user is able to enable/disable Hik-Connect service. Admin account user is able to view verification code for Hik-Connect service on web browser or iVMS-4200.
- Time zones of particular areas are updated: Istanbul is changed to GMT+3:00 and Novosibirsk

is changed to GMT+7:00.

- In DST configuration of French web page, the typo of Tuesday and Thursday is corrected.
- Intrusion detection and line crossing detection alarm types are available on Hik-Connect service.

Note: Intrusion detection and line crossing detection rules should be configured on web browser, iVMS client or NVR after enabling Alarm Notification on Hik-Connect APP.

- It supports to check the password when login in via Web.



Customer Impact and Recommended Action

This update refers to function/compatibility improvement and will take effect automatically after the Date of Change. We are very sorry for any inconvenience of use-habit changes caused by this action. For any questions and request for this firmware, please contact our local technical support team.

Remarks:

- Hikvision reserves the right to change, alter or withdraw the above notification without prior notice.
- Product design and specifications are subject to change without prior notice.
- The Hikvision firmware may contain defects or errors known as errata which may cause the product to deviate from published specifications. Current characterized errata are available on request.
- Hikvision is not liable for any typing or printing errors.

Hikvision Digital Technology CO., Ltd.

No. 555 Qianmo Road, Binjiang District, Hangzhou 310051, China

Tel: +86-571-8807-5998

FAX: +86-571-8993-5635

Email: overseabusiness@hikvision.com

Supported Product List R7

Product Category	Model Number	Product Description
Bullet Camera	DS-2CD4B16FWD-IZ(S)	1.3MP, WDR
Bullet Camera	DS-2CD4B26FWD-IZ(S)	2MP, WDR
Bullet Camera	DS-2CD4B36FWD-IZ(S)	3MP, WDR
Box camera	DS-2CD4C26FWD-(A)(P)	2MP, WDR
Box camera	DS-2CD4C36FWD-(A)(P)	3MP, WDR
Dome camera	DS-2CD4D16FWD-IZ(S)	1.3MP, WDR
Dome camera	DS-2CD4D26FWD-IZ(S)	2MP, WDR
Dome camera	DS-2CD4D36FWD-IZ(S)	3MP, WDR
Bullet camera	DS-2CD4A26EFWD-IZ(H)(S)	2MP, WDR
Dome camera	DS-2CD4126EFWD-IZ	2MP, WDR
Box camera	DS-2CD4026EFWD	2MP, WDR
Box camera	DS-2CD4A24FWD-IZ(H)(S)(B)(4.7-94mm)	2MP, Long focal distance
Mobile Camera	DS-2XM6112FWD-I(M)	1.3MP, WDR
Mobile Camera	DS-2XM6122FWD-I(M)	2MP, WDR
Mobile Camera	DS-2CD6512-I(O)	1.3MP, IR
Mobile Camera	DS-2CD6512DT-I(O)	1.3MP, IR
Mobile Camera	DS-2CD6522-I(O)	2MP, IR
Mobile Camera	DS-2CD6522DT-I(O)	2MP, IR